

Doc. No.: SDS - 001B (2)
Page: Page 1 of 6

Owner: Safety & Quality

Rev. Date: July 18, 2016

Argon (Refrigerated)

1 IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Trade name : Argon (Refrigerated)

SDS No. : 001B
Chemical Formula : Ar

Company Identification : Air Liquide Philippines Inc.

Main Office : 12F Ecotower, 32nd St. cor. 9th Ave., Bonifacio Global City,

Taguig City 1634, Philippines

Main Plant : Sandoval Ave., Pinagbuhatan, Pasig City

Phone No. : (02) 838 – 1780 to 83 / 837-8135 to 37 / 838-1756

: 09189168312 (Customer hotline 6PM-8AM)

2 HAZARDS IDENTIFICATION

Classification of the substance

• Physical Hazard : Gases under pressure - Refrigerated liquefied gas

• **Health Hazard** : no acute toxicity

Label Elements

Hazard Pictogram



Signal word : Warning

Hazard Statement : Contact of product can cause cryogenic burns or injury

• Precautionary statements

Prevention
 Response
 Wear cold insulating gloves / face shield / eye protection
 Thaw frosted parts with lukewarm water. Do not rub affected

area

: Get immediate medical advice / attention : Get immediate medical advice/attention.

Storage : Store in a well ventilated area

Other Hazard

Other hazards : Refrigerated liquefied gas. Contact with product may cause

cold burns or frostbite.

: In high concentration may cause asphyxiation

Customer Hotline - 6PM-8AM:

Phone No.:

(02) 838-1780-83

0918 916 8312



Doc. No.: SDS - 001B (2)

Page: Page 2 of 6

Safety & Quality

Owner:

Rev. Date: July 18, 2016

Argon (Refrigerated)

3 COMPOSITION / INFORMATION ON INGREDIENTS

Substance / Preparation : Substance

Substance Name Contents CAS No. EC No. Index No. Classification Argon (Refrigerated) 100% 7440-37-1 231-147-0 ------

Contains no other components or impurities which will influence the classification of the product.

4 FIRST AID MEASURES

First Aid Measures

- Inhalation : In high concentrations may cause asphyxiation. Symptoms may include loss

of mobility / consciousness. Victim may not be aware of asphyxiation

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial

respiration if breathing stopped.

- Skin / Eye Contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

In case of frostbite spray with water for at least 15 minutes. Apply a sterile

dressing. Obtain medical assistance.

- **Ingestion** : Ingestion is not considered a potential route of exposure.

5 FIRE FIGHTING MEASURES

Flammable class : Non flammable

Specific hazards : Exposure to fire may cause containers to rupture / explode

Hazardous Combustion Products : None

Extinguishing media

Suitable extinguishing media : All known extinguishants can be used.

Specific methods : If possible stop flow of product.

Move away from the container and cool with water from a protected position. If leaking do not spray water onto container. Water surrounding area (from protected position) to contain

Phone No.:

Customer Hotline - 6PM-8AM:

(02) 838-1780-83

0918 916 8312

fire.

Special protective equipment for

fire fighters

: In confined space use self-contained breathing

apparatus



SDS - 001B (2) Doc. No.: Page 3 of 6 Page:

Owner: Safety & Quality

Rev. Date: July 18, 2016

Argon (Refrigerated)

6 ACCIDENTAL RELEASE MEASURES

Personal precautions : Evacuate area

Use protective clothing

Wear self-contained breathing apparatus when entering area

unless atmosphere is proved to be safe.

Ensure adequate air ventilation.

Environmental Precautions : Try to stop release.

Prevent from entering sewers, basements and workpits, or any

place where its accumulation can be dangerous.

Clean up methods : Ventilate area.

7 HANDLING AND STORAGE

Storage : Keep container below 50 degrees C in a well ventilated place.

Handling : Suck back of water into the container must be prevented

Do not allow backfeed into the container.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas

supplier if in doubt.

Refer to supplier's container handling instructions.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Measures/Controls : Good general ventilation should be used. Ventilation rates

> should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-

proof - electrical, ventilating and/or lighting equipment.

Personal Protective Equipment

Respiratory : In case of insufficient ventilation, wear suitable respiratory

equipment.

: Wear safety glasses. Eye/Face

Skin/Body : Wear leather gloves when handling cylinders.

:Follow best practice for site management and disposal of **Environmental Exposure Controls**

waste. Controls should be engineered to prevent release to the

Phone No.:

(02) 838-1780-83

0918 916 8312

environment, including procedures to prevent spills,

Customer Hotline - 6PM-8AM:

atmospheric release and release to waterways.



Doc. No.: SDS - 001B (2)
Page: Page 4 of 6

Owner: Safety & Quality

Rev. Date: July 18, 2016

Argon (Refrigerated)

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 degrees C : Refrigerated liquefied gas.

Color : Colorless liquid

Odor : No odor warning properties

Molecular Weight : 40

Melting point (degrees C) : - 189

Boiling point (degrees C) : - 186

Critical temperature (degrees C) : - 122

Vapor pressure, 20 degrees C : Not Applicable

Relative density, gas (air =1) : 1.38
Relative density, liquid (water = 1) : 1.4
Solubility in water [mg/l] : 67

Flammability range [vol% in air] : Non flammable

Other data : Gas/vapor heavier than air. May accumulate in confined

spaces, particularly at or below ground level.

10 STABILITY AND REACTIVITY

Stability and reactivity : Stable under normal conditions.

Liquid spillages can cause embrittlement of structural

materials.

11 TOXICOLOGICAL INFORMATION

Toxicity information : No known toxicological effects from this product

12 ECOLOGICAL INFORMATION

Ecological effects information : Can cause frost damage to vegetation.

13 DISPOSAL CONSIDERATIONS

General : Do not discharge into any place where its accumulation could

be dangerous

Contact supplier if guidance is required.

AIR LIQUIDE PHILIPPINES INC.12F Ecotower, 32nd St. cor. 9th Ave., Bonifacio Global City, Taguig City

Phone No. : (02) 838-1780-83 Customer Hotline – 6PM-8AM : 0918 916 8312



Doc. No.: SDS - 001B (2)
Page: Page 5 of 6

Owner: Safety & Quality

Rev. Date: July 18, 2016

Argon (Refrigerated)

14 TRANSPORT INFORMATION

UN No. : 1951 H.I. nr : 22 ADR / RID

- Proper shipping name

- ADR Class - ADR / RID Classification code : 3 A

- Labelling ADR



: 2.2: Non flammable, non toxic gas.

: ARGON, REFRIGERATED LIQUID

Other transport information

: Avoid transport on vehicles where the load space is not separated from the driver's compartment

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

Phone No.:

Customer Hotline - 6PM-8AM:

(02) 838-1780-83

0918 916 8312

- Ensure there is adequate ventilation.
- Compliance with applicable regulations

15 REGULATORY INFORMATION

EC Classification : Not included in Annex I.

Not classified as dangerous preparation / substance

EC Labeling : No EC labeling required.

- Symbol (s) : None
- R Phrase (s) : None
- S Phrase (s) : None



Doc. No.: SDS - 001B (2)

Safety & Quality

Page: Page 6 of 6

Owner:

Rev. Date: July 18, 2016

Argon (Refrigerated)

16 OTHER INFORMATION

- Asphyxiant in high concentrations.
- Keep container in a well-ventilated place.
- Do not breathe the gas.
- May cause frostbite.
- Wear suitable protective clothing.
- Ensure all national / local regulations are observed.
- The hazard of asphyxiation is often overlooked and must be stressed during operator training.
- This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.
- Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
- Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Recommended uses and restrictions:

This SDS is for information purposes only and is subject to change without prior notice. [Prior to purchase of products, please contact your local AIR LIQUIDE office for the latest SDS edition].

End of Document

(02) 838-1780-83

0918 916 8312

Phone No.:

Customer Hotline - 6PM-8AM: